


# BUILD SOLUTIONS






2020



# PROSSIVE 9000 EPDM SERIES



- It has high adhesion strength for sound and waterproofing applications.
- It can be produced with or without modified acrylic adhesive on one or both sides.
- It has black EPDM sponge structure with different density options.



# PROSSIVE 10707 BUTYL TAPE



- It has high adhesion strength for insulation purposes.
- Easy to apply with its elastic structure, -30°C ~ +80°C heat resistant.
- It provides air and moisture impermeability at the connection points of galvanized sheet and aluminum profile



# PROSSIVE IMPREGNATED JOINT SEAL. TAPE




- Impregnated joint sealing tape suitable for use around joinery, in a wide variety of moving joints and other applications
- For waterproofing, gap filling, sound insulation and joint filling applications in structural structures



# PROSSIVE 1301 PVC TAPE



- Low friction, easy to remove and leave no marks.
- PVC tape with high UV resistance, suitable for fixing plastic and metal parts.



# PROSSIVE 7802 PVB PROTECTION TAPE



- It prevents the deterioration of the PVB layer that will occur over time in laminated glass and the laminated glass from being out of warranty by making it long-lasting..
- It is a PVB layer protection solution in laminated glass railings used in shopping malls, parks and balconies..
- It is UV resistant and impermeable with 0.8mm wall thickness.

## PROSSIVE PROPROOF 9558



- Roofing, floor, buffer zone etc. Tape that can be applied even at -20 ° C with a single sided high performance adhesive for applications of TPO, membrane joint and end closure materials used in places.

## PROSSIVE KC 9480



- Metali aluminum etc. Scratches, abrasion etc. that may occur during transportation on the surfaces of material handling benches and conveyed materials. ensures that situations are eliminated.
- High performance and heat resistant adhesive felt tape.

# PROSSIVE PE FOAM FAMILY



**5310 Series**

- ✔ Suitable for indoor and outdoor applications.
- ✔ PE tape with an acrylic adhesive
- ✔ PE 1,0 mm thickness with black and White color options.
- ✔ It's resistant to 90°C temperature with single and double sided adhesive options.



**5310 WL**



**5310 BL**




**5420 Series**

- ✔ Suitable for indoor and outdoor applications.
- ✔ PE tape with an acrylic adhesive
- ✔ PE 2,0 mm thickness with black and White color options.
- ✔ It's resistant to 90°C temperature with single and double sided adhesive options.



**5420 BL**



**5421 BL**



**5430 Series**

- ✔ Suitable for indoor and outdoor applications.
- ✔ PE tape with an acrylic adhesive
- ✔ PE 3,0 mm thickness with black and White color options.
- ✔ It's resistant to 90°C temperature with single and double sided adhesive options.



**5430 BL**




**5431 BL**

# PROSSIVE SAT TAPES




- It is used as an alternative to all joining methods such as rivets, screws, and welding.
- It has 1,0mm and 0,5mm options and it's transparent color. It provides sealing and insulation.
- Provides design freedom and has vibration and damping properties.



# ORAFOL UHB TAPES



- It is used as an alternative to all joining methods such as rivets, screws, and welding.
- It has different thicknesses such as 0.25mm, 0.40mm, 0.5mm, 0.64mm, 1mm, 1.5mm, 2mm.
- It has transparent, white, black and gray color options; It provides sealing and insulation.



# 3M VHB TAPES



- It has different thicknesses such as 0.25mm, 0.5mm, 1mm, 1.5mm, 2mm and 2.3mm.
- It has a heat resistance of 240 ° C; It is resistant to severe conditions such as corrosion, chemicals and moisture.
- It's suitable for combining different surfaces and provides design freedom.
- It has transparent, white, black and gray color options.
- It is suitable for bonding applications, composite back tension panel bonding, exterior decorative profile bonding and galvanized sheet joining processes.



**9473**



**4905 F**




**4910 F**



**GPH 110**



**4950 P**




**5952 F**



**4979 F**



**4991 F**



**B 23 F**

## PROSSIVE 7722 SG



- It provides the opportunity to use at the junction points of Office partition glasses without the need for H ptofile.
- It's a 2 mm thickness, ultra transparent one side adhesive tape with no adhesive edges.



## 3M 8777 FLASHING TAPE




- Weather, moisture, etc. around windows, doors and wooden frames. provides sealing.
- Suitable for membrane joint joint, blind casing waterproofing, under concrete insulation in balconies, terraces and corner turns.
- It provides adhesion to difficult surfaces such as all kinds of brick and concrete at -20 ° C.



## 3M 4412 EXTREME SEALING TAPE



- It eliminates the water leakage problem on the roofs with fast, clean and practical application.
- It has high heat resistance and can be painted over.
- Single sided tape with an elastic and soft texture, superior adhesion performance.





# SIKA SIKAFLEX 545



- Tile, ceramic glass mosaic, marble, granite, etc. It is a cement-based, waterproof joint filling material that is used as joint filler for coatings, resistant to thermal expansion and contraction and vibration.

# SIKA SIKAFLEX 221



- Multi-purpose polyurethane sealant adhesive with high yield strength, suitable for many surfaces.
- It is resistant to aging, elastic structure, impermeable.
- It is odorless and NFS approved. It has white, gray, black and brown color options.

# SIKA 5211 NT



- It is a two-component acrylic adhesive that provides alternative joints instead of rivets, screws and welding.
- It has the ability to be adhered, painted and sanded to many surfaces without treatment.
- It has white, gray and black color options and does not contain isocyanate and solvent.

# SIKA SIKASIL 670 FIRE



- It is single component, fire resistant. It provides sealing.
- Fire resistance up to 5 hours in accordance with EN 1366-4 and fire resistance up to 2 hours in accordance with EN 1366-3.

# SIKA SG500



- It is a two component structural silicone adhesive.
- It is suitable for bonding applications, solar panel module assembly processes.
- Fire resistant (EN 11925-2 / DIN 4102-B1)
- Provides high resistance to difficult weather conditions.

# SIKA SIKASIL WS 305CN



- It is one component, does not contain solvent.
- It is a very fast curing sealant silicone that can be applied at low and high temperatures.
- It provides high resistance to outdoor weather conditions and UV.
- It is produced especially for the insulation of building and curtain wall systems.
- It does not stain glass and metal surfaces, and is compatible with water and solvent-based paints.

## SIKA SIKASIL SG 20




- It is a structural silicone with resistance and flexibility properties.
- It provides high adhesion and cures with moisture.
- It is used for adhesion in aluminum frame-glass manufacturing in structural facades.

## SIKA SIKASIL WS-605 S




- It is a neutral curing sealant. It provides excellent adhesion to many different surfaces.
- Suitable for use in structural glazing and facade cladding systems.
- It has excellent resistance to UV rays and environmental conditions.
- Does not flow after curing.

## 3M 2542 VIBRATION DAMPING TAPE



- It provides sound absorption by applying to panels and support elements where vibration is present.
- It has high strength.
- It eliminates vibration and noise problems with compressed viscoelastic polymer and aluminum foil.



## 3M 540 HYBRID



- High performance, one component, ambient moisture curing, polyurethane sealant suitable for construction applications.
- It cures fast.
- It provides adhesion for approximately 45-60 minutes.

## 3M 760 HYBRID



- It is a single component, modified polymer sealant, UV resistant, hybrid adhesive that forms permanent elastic bonds, suitable for trucks, trains, interior-exterior panels.
- Hybrid technology can be painted when wet and will not deteriorate while exposed to infrared rays.
- It has 30 minutes of crusting time.
- Used for joining and sealing materials such as concrete, wood, aluminum, polyester, glass, stone, ceramics.

## 3M PR 100



- It is a fast adhesive suitable for plastic and rubber bonding, freezing in 3-5 seconds.
- It's suitable for joining applications of rubber seals on the joinery edge.

# CAULO SOLID STEPS 8998



- It is an non-slip floor coating that can be applied to concrete, epoxy and many difficult surfaces.
- With it's special formula, it provides good adhesion to the surface with high bonding.
- It can be applied in the desired width and shape with it's spreadable feature and provides design freedom with different color options.
- It is resistant to abrasion, UV and chemical.
- It is not affected by rain, snow,water etc. Conditions.



# CAULO 90080 INDUSTRIAL CLEANER




- It provides surface cleaning in cases of dirt, oil, residue, etc. that occur on many different surfaces.
- It allows labels, stickers, adhesive tapes and residue to be easily removed from the surface. Effortlessly remove price tags.


# PROSSIVE 1660 FLOCK TAPE



- It's a fabric tape with one side adhesive, suitable for surface coating processes.
- It's modified acrylic adhesive and it has the ability to be produced with or without mesh reinforcement.
- It has black, gray, beige, red and dark blue color options.



# VELCRO 6411 ALFA -LOK




- It is an adhesive backed, removable fixing system.
- It can carry 12 N/cm load with its high strength adhesive and the strength of its plastic teeth.



# VELCRO HOOK & LOOP




- It is an adhesive backed, removable fixing system.
- One side female and one side male fabric tape with high strength adhesive.




# SPECIAL CUTTING SOLUTIONS



- Special cutting processes for projects, providing ease of application
- Slitting, laminating, diecut, kisscut, spool winding, extended liner (fingerlift), sheeting, laser cutting, applicator design processes are made according to the project requirements.



**SLITTING**



**LAMINATION**



**DIECUT**



**KISSCUT**



**SPOOL WINDING**



**EXTENDED LINER**



**SHEETING**



**LASER CUTTING**



**APPLICATOR  
DESIGN**





**Proslime Kimya San. Tic. A.Ş.**  
Ferhatpaşa Mah. 91. Sk No : 20  
Ataşehir / İstanbul  
Tel: 0216 266 66 76  
[www.proslime.com.tr](http://www.proslime.com.tr)  
[info@proslime.com.tr](mailto:info@proslime.com.tr)

